





C6110047133

(SP4802-1P)

## **TWISTED SPEAKER CABLE**



### **DESCRIPTION**

16AWG., 1.5mmsq. Stranded TACW, Twisted Pair, PVC Insulation, PVC Sheath.

### **APPLICATION**

For the connecting wiring between the amplifier & speaker.

### **APPLICABLE STANDARD**

- RoHS 2011/65/EU Directive.

### **CONSTRUCTION**

#### **Conductor**

Material :	Tinned Annealed Copper Wire
Size :	1.5mmsq. (16AWG)
Construction :	Stranded (48/0.2mm)

#### **Insulation**

Material :	PVC
Nominal O.D :	2.9mm
Color :	Black, White

All values subject to factory tolerances.

Samson tries to ensure accuracy at the time of issue and reserves the right to change the data of the products without notice.

Copyright © 2013 Samson Electric Wire Co., Ltd. All Rights Reserved.

Establish : LLS | Approved : LQM | Issue : 01 | Date : 18-02-2016 | Page 1 of 2



C6110047133

(SP4802-1P)

## **TWISTED SPEAKER CABLE**

### **Sheath**

Material :	PVC
Nominal O.D :	7.2mm
Color :	Grey

### **PHYSICAL PROPERTIES**

Operating Temperature (Flexing)	-15°C to 70°C
Operating Temperature (Fixed)	-30°C to 70°C
Min. Bend Radius (Fixed)	72mm

### **ELECTRICAL PROPERTIES**

Rated Voltage	300V
Max. Suggest Current	9A
Max. DCR @20°C	13.7Ω/km
Voltage test : Core to Core	2kV a.c/1min

All values subject to factory tolerances.

Samson tries to ensure accuracy at the time of issue and reserves the right to change the data of the products without notice.

Copyright © 2013 Samson Electric Wire Co., Ltd. All Rights Reserved.

Establish : LLS | Approved : LQM | Issue : 01 | Date : 18-02-2016 | Page 2 of 2