


C2010063111

(RG59BU(84%))

75ohm Coaxial Cable RG59 22AWG, PVC Sheath



DESCRIPTION

22AWG Solid CCS, Solid PE Insulation, PACW Braiding 84% Coverage, PVC Sheath.

APPLICATION

For CATV/MATV, Broadband, HDTV and Satellite Broadcasting Transmission use.

APPLICABLE STANDARD

- EU RoHS Complies 2011/65/EU
- Equivalent to Belden 9244
- AWM Style 1354

CONSTRUCTION

Conductor

Material :	Copper Clad Steel Wire
Size :	22AWG
Construction :	Solid (1/0.643mm)

Insulation

Material :	Solid PE
Nominal O.D :	3.7mm

Braiding

Material :	Plain Annealed Copper Wire, 84% Coverage
------------	--

All values subject to factory tolerances.

Samson tries to ensure accuracy at the time of issue and reserves the right to change the data of the products without notice.

Copyright © 2013 Samson Electric Wire Co., Ltd. All Rights Reserved.

Establish : YDM | Approved : LQM | Issue : 05 | Date : 25-11-2015 | Page 1 of 2



C2010063111 (RG59BU(84%))
75ohm Coaxial Cable RG59 22AWG, PVC Sheath

Sheath

Material :	PVC
Nominal O.D :	6.2mm
Color :	Black

PHYSICAL PROPERTIES

Operating Temperature (Flexing)	-15°C to 80°C
Operating Temperature (Fixed)	-30°C to 80°C
Min. Bend Radius	62mm
Flame Test	UL1581 FT-1

ELECTRICAL PROPERTIES

Rated Voltage	30V
Max. Conductor DC Resistance @20°C	221.3Ω/km
Voltage test : Core to Shielding	2000V a.c/1min
Nom. Characteristic Impedance	75±3Ω (10MHz)
Nom. Capacitance	67±2pF/m (1KHz)
Max. Attenuation (dB/100m)	

(MHz)	1	10	50	100	200	400	700	900	1000
(dB)	2.0	3.7	8.3	11.5	16.5	23.7	32.5	37.2	40.2

All values subject to factory tolerances.

Samson tries to ensure accuracy at the time of issue and reserves the right to change the data of the products without notice.

Copyright © 2013 Samson Electric Wire Co., Ltd. All Rights Reserved.

Establish : YDM | Approved : LQM | Issue : 05 | Date : 25-11-2015 | Page 2 of 2